

Dated 19th July, 1994 for all buildings following additional conditions shall apply.

- i) As soon as the development permission for new construction or re-development is obtained by the Owners/Developer, he shall install a 'Display Board' on the conspicuous place on site indicating following details :-
 - a) Name and address of the owner/developer, Architect and Contractor.
 - b) Survey Number/City survey Number, Plot Number/Sector & Node of Land under reference along with description of its boundaries.
 - c) Order Number and date of grant of development permission or re-development permission issued by the Planning Authority or any other authority.
 - d) Number of Residential flats/Commercial Units with areas.
 - e) Address where copies of detailed approved plans shall be available for inspection.
 - ii) A notice in the form of an advertisement, giving all the detailed mentioned in (i) above, shall be published in two widely circulated newspapers one of which should be in regional language.
11. As directed by the Urban Development Deptt. Government of Maharashtra, under Section -154 of MR & TP Act- 1966 and vide Provision No. TPB 432001/2133/CR-230/01/UD-11,dated 10/03/2005, for all buildings, greater than 300.00 Sq. m. following additional condition of Rain Water Harvesting shall apply.
- a) All the layout open spaces/amenities spaces of Housing Society and new construction /reconstruction / additions on plots having area not less than 300.00 Sq. m. shall have one or more Rain Water Harvesting structures having minimum total capacity as detailed in schedule (enclosed).
- Provided that the authority may approve the Rain water Harvesting Structures of specifications different from those in Schedule, subject to the minimum capacity of Rain Water Harvesting being ensured in each case.
- b) The owner/society of every building mentioned in the (a) above shall ensure that the Rain

Document certified by PATIL MITHILESH
JANARDHAN <mithilesh.patil@gmail.com>.

Name : PATIL MITHILESH
JANARDHAN
Designation : Associate
Planner
Organization : CIDCO

Water Harvesting structure is maintained in good repair for storage of water for non potable purposes or recharge of groundwater at all times.

- c) The Authority may impose a levy of not exceeding Rs. 100/- per annum for every 100 Sq. m. of built up area for the failure of the owner of any building mentioned in the (a) above to provide or to maintain Rain Water Harvesting structures as required under these byelaws.



Document certified by PATIL MITHILESH
JANARDHAN <mithilesh.patil@gmail.com>.

Name : PATIL MITHILESH
JANARDHAN
Designation : Associate
Planner
Organization : CIDCO

SCHEDULE**RAIN WATER HARVESTING**

Rain Water Harvesting in a building includes storage or recharging into ground of rain water falling on the terrace or any paved or unpaved surface within the building site.

1. The following systems may be adopted for harvesting the rain water drain from the terrace and the paved surface.

- i) Open Well of a minimum 1.00 mt. dia. And 6 mt. in depth into which rain water may be channelled and allowed after filtration for removing silt and floating material. The well shall be provided with ventilating covers. The water from the open well may be used for non-potable domestic purposes such as washing, flushing and for watering the garden etc.
- ii) Rain water harvesting for recharge of ground water may be done through a bore well around which a pit of one metre width may be excavated up to a depth of at least 3.00 mt. and refilled with stone aggregate and sand. The filtered rain water may be channelled to the refilled pit for recharging the bore well.
- iii) An impervious surface/ underground storage tank of required capacity may be constructed in the setback or other open space and the rain water may be channelled to the storage tank. The storage tank shall always be provided with ventilating covers and shall have draw-off taps suitably placed so that the rain water may be drawn off for domestic, washing, gardening and such other purposes. The storage tanks shall be provided with an overflow.
- iv) The surplus rain water after storage may be recharged into ground through percolation pits or trenches or combination of pits and trenches. Depending on the geomorphological and topographical condition, the pits may be of the size of 1.2 mt. width X 1.2 mt. length X 2 mt. to 2.5 mt. depth. The trenches can be of 0.6 mt. width X 2 to 6mt. length X 1.5 to 2 mt depth. Terrace water shall be channelled to pits or trenches. Such pits or trenches shall be back filled with filter media comprising the following materials.
 - a) 40 mm stone aggregate as bottom layer up to 50% of the depth.

Document certified by PATIL MITHILESH
JANARDHAN <mithilesh.patil@gmail.com>.

Name : PATIL MITHILESH
JANARDHAN
Designation : Associate
Planner
Organization : CIDCO