## SPECIFICATIONS FOR GR SITARA

1	
STRUCTURE	RCC framed structure
& WALLS	Concrete 6"/4" Solid Block Masonry walls
	All Internal walls smoothly Plastered with Lime rendering.
	External plastering with sponge finish
	Main Door Frame is of Teak Wood and internal door frames will be of
	Hardwood.
	The Main door will be of Teak Veneer Flush Shutter and internal doors
DOORS &	shall be of block board with synthetic enamel paint finish.
WINDOWS	Windows and French windows shall be in UPVC sliding with clear float
WINDOWS	Glass.
	Aluminium Ventilator for Toilets
	Additinuity vendiator for Foliets
	Fire Resistant electrical wire of Anchor/equivalent.
ELECTRTICAL	Elegant modular electrical switches.
	Telephone and Television points in living and Master bedroom.
	Vitrified flooring in living, dining, kitchen, and Bedroom
	Laminated Wooden Flooring for the Master Bedroom
FLOORING	Ceramic tile flooring for Balcony and Utility.
	Elegant entrance lobbies of Anti-Skid Tiles.
	All Corridors will be with Anti-Skid Tiles and Staircases will be with
	Granite.
	Ceramic Glazed tiles dado up to a height of 7 feet in all toilets.
	Hindware/Vitra or equivalent make sanitary ware.
TOILETS	C.P. Fitting Jaquar Continental make/Vitra or Equivalent except health
	faucet.
	<ul> <li>Plumbing concealed in C.P.V.C./P.V.C Pipes. All external plumbing,</li> </ul>
	waste water pipes and storm water drains shall be in combination of
	PVC and Stoneware pipes.
KITCHEN	20mm Black granite kitchen platform, and stainless steel sink will be
. C. C. L.	supplied.
	<ul> <li>2 feet glazed ceramic tiles dado above granite kitchen platform unit will</li> </ul>
	be supplied.
	<ul> <li>Provision for washing machine.</li> </ul>
PAINITING	Interior – Base white oil bound/acrylic distemper.
I VIIII IIIO	<ul> <li>Exterior - Cement based paint equivalent shall be used.</li> </ul>
	Description of the state of the
	Doors — The main door shall be provided with Melamine Polish. All other doors shall be provided with synthetic enamel paint.
	M.S. Grills and railings – Paint to M.S. grills and railings shall be in
	synthetic enamel paint.
LIET	·
LIFT	Lift of reputed make SCHINDLER / OTIS / KONE or equivalent.
GENERATOR	Generator backup for common areas, lifts, pumps and 0.5KVA for
GLINLINATUR	
	Lighting to each flat.