Reference No.: CIDCO/BP-16781/TPO(NM & K)/2019/4906 Date: 22/6/2019

## **COMMENCEMENT CERTIFICATE**

Permission is hereby granted under section - 45 of the Maharashtra Regional and Town Planning Act. 1966 (MaharashtraXXXVII) of 1966 to M/s Shri.Rohidas Laxman Mokal., House No-233A, At-Targhar,Post-Ulwa,Tal-Panvel,Dist-Raigad. for Plot No. 9, Sector 25, Node Pushpak(New). As per the approved plans and subject to the following conditions for the development work of the proposed Residential [ Resi+Comm ] + Mercantile / Business (Commercial) [ Resi+Comm ] in 1Ground Floor + 4Floor Net Builtup Area [Residential [ Resi+Comm ] =291.23,Mercantile / Business (Commercial) [ Resi+Comm ] =21.65 Total BUA = 312.88] Sq m.

Nos. Of Residential Units :- 11, Nos. Of Mercantile / Business (Commercial) Units :- 2

- A. This Commencement Certificate is valid up to plinth level only. The further order will be given after the plinth is inspected and plinth Completion Certificate is issued.
- B.Applicant Should Construct Hutments for labors at site.

C.Applicant should provide drinking water and toilet facility for labors at site.

# 1. This Certificate is liable to be revoked by the Corporation if :-

- 1(a) The development work in respect of which permission is granted under this certificate is not carried out or the use thereof is not in accordance with the Sanctioned plans.
- 1(b) Any of the conditions subject to which the same is granted or any of the restrictions imposed upon by the corporation is contravened.
- 1(c) The Managing Director is satisfied that the same is obtained by the applicant through fraud or Misrepresentation and the applicant and/or any person deriving title under him, in such an event shall be deemed to have carried out the development work in contravention of section - 43 or 45 of the Maharashtra Regional and Town Planning Act- 1966.
- 2. The applicant shall :-

Document certified by PATIL MITHILESH
JANARDHAN <a href="mithilesh.pathagmail.com">mithilesh.pathagmail.com</a>
Name: PATIL MITHILESH
JANARDHAN
Designation
Planner
Organization: CIDCO

Reference No.: CIDCO/BP-16781/TPO(NM & K)/2019/4906 Date: 22/6/2019

2(a) Give a notice to the Corporation for completion of development work upto plinth level, a least 7 days before the commencement of the further work.

- 2(b) Give written notice to the Corporation regarding completion of the work.
- 2(c) Obtain Occupancy Certificate from the Corporation.
- 2(d) Permit authorized officers of the Corporation to enter the building or premises for which th permission has been granted, at any time for the purpose of ensuring the building contri Regulations and conditions of this certificate.
- The Certificate shall remain valid for period of 1 year from the date of its issue, thereafter revalidation of the same shall be done in accordance with provision of Section 48 of MRTP Ad 1966 and as per regulations no. 16.1(2) of the GDCRs 1975.
- The conditions of this certificate shall be binding not only on the applicant but also on it successors and/or every person deriving title through or under him.
- 5. A certified copy of the approved plan shall be exhibited on site.
- 6. The amount of **Rs**I-deposited with CIDCO as security deposit shall be forfeited either in whole or in part at the absolute discretion of the Corporation for breach of any of the conditions attached to the permission covered by the Commencement Certificate. Such forfeiture shall be without prejudice to any other remedy or right of Corporation.
- 7. "Every Building shall be provided with underground and over head water tank. The capacity of the tanks shall be as per norms fixed by CIDCO. In case of high rise buildings underground and over head water tank shall be provided as per the fire fighting requirements of CIDCO. The applicant shall seek approval of the EE (Water Supply) of CIDCO in respect of capacity of domestic water tanks. The applicant shall seek approval of the Fire Officer of CIDCO in respect of capacity of water tanks for the fire fighting purpose".
- 8. You shall approach Executive Engineer, M.S.E.B. for the power requirements, location of transformer, if any, etc.

Document certified by PATIL MITHILESH JANAROHAN <a href="mithilesh.paylognail.com">mithilesh.paylognail.com</a>

Name : PATIL MTTALE: JANARDIAN Designation Associate Planner Organization : CIDCO Reference No. : CIDCO/BP-16781/TPO(NM & K)/2019/4906 Date : 22/6/2019

9 As per Govt. of Maharashtra memorandum vide no. TBP/4393/1504/C4-287/94, UD-11/RE Dated 19<sup>th</sup> July, 1994 for all buildings following additional conditions shall apply.

- i) As soon as the development permission for new construction or re-development obtained by the Owners/Developer, he shall install a 'Display Board' on the conspicuou place on site indicating following details;-
- Name and address of the owner/developer, Architect and Contractor.
- b) Survey Number/City survey Number, Plot Number/Sector & Node of Land under reference along with description of its boundaries.
- c) Order Number and date of grant of development permission or re-development permissio issued by the Planning Authority or any other authority.
- d) Number of Residential flats/Commercial Units with areas.
- e) Address where copies of detailed approved plans shall be available for inspection.
- ii) A notice in the form of an advertisement, giving all the detailed mentioned in (i) above shall be published in two widely circulated newspapers one of which should be in regional language.
- 11. As directed by the Urban Development Deptt. Government of Maharashtra, under Section -154 of MR & TP Act- 1966 and vide Provision No. TPB 432001/2133/CR-230/01/UD-11,dated 10/03/2005, for all buildings, greater than 300.00 Sq. m. following additional condition of Rain Water Harvesting shall apply.
- a) All the layout open spaces/amenities spaces of Housing Society and new construction / reconstruction / additions on plots having area not less than 300.00 Sq. m. shall have one or more Rain Water Harvesting structures having minimum total capacity as detailed in schedule (enclosed).

Provided that the authority may approve the Rain water Harvesting Structures of specifications different from those in Schedule, subject to the minimum capacity of Rain Water Harvesting being ensured in each case.

Document certified by PATIL MITHILESH JANARDHAN <mithilesh page mail.com

Name: PATIL MODILESH JANARDIAN Designation Cociate Planner Organization: CIDCO Reference No. : CIDCO/BP-16781/TPO(NM & K)/2019/4906 Date : 22/6/2019

b) The owner/society of every building mentioned in the (a) above shall ensure that the Rai Water Harvesting structure is maintained in good repair for storage of water for non potabl purposes or recharge of groundwater at all times.

c) The Authority may Impose a levy of not exceeding Rs. 100/- per annum for every 100 Sq m. of built up area for the failure of the owner of any building mentioned in the (a) above to provide or to maintain Rain Water Harvesting structures as required under these byelaws.

Document certified by PATIL MITHILESH JANARDHAN <a href="mithilesh.page">JANARDHAN <a href="mithilesh.page">mithilesh.page</a>gmail.com>

Name: PATIL MITTLESH
JANARDIAN
Designation
Planner
Organization: CIDCO

Reference No.: CIDCO/BP-16781/TPO(NM & K)/2019/4906

Date: 22/6/2019

#### SCHEDULE

### RAIN WATER HARVESTING

Rain Water Harvesting in a building includes storage or recharging into ground of rain water fallin on the terrace or any paved or unpaved surface within the building site.

- The following systems may be adopted for harvesting the rain water drain from the terrace ar
  the paved surface.
  - i) Open Well of a minimum 1.00 mt. dia. And 6 mt. in depth into which rain water may be channelled and allowed after filtration for removing silt and floating material. The well show the provided with ventilating covers. The water from the open well may be used for nor potable domestic purposes such as washing, flushing and for watering the garden etc.
  - ii) Rain water harvesting for recharge of ground water may be done through a bore we around which a pit of one metre width may be excavated up to a depth of at least 3.00 ml and refilled with stone aggregate and sand. The filtered rain water may be channelled to the refilled pit for recharging the bore well.
  - iii) An impervious surface/ underground storage tank of required capacity may be constructe in the setback or other open space and the rain water may be channelled to the storage tank. The storage tank shall always be provided with ventilating covers and shall have draw off taps suitably placed so that the rain water may be drawn off for domestic, washing gardening and such other purposes. The storage tanks shall be provided with an overflow.
  - iv) The surplus rain water after storage may be recharged into ground through percolation pit or trenches or combination of pits and trenches. Depending on the geomorphological antopographical condition, the pits may be of the size of 1.2 mt. width X 1.2 mt. length X 1 mt. to 2.5 mt.depth. The trenches can be of 0.6 mt. width X 2 to 6mt. length X 1.5 to 2 mtdepth. Terrace water shall be channelled to pits or trenches. Such pits or trenches shall be back filled with filter media comprising the following materials.
    - a) 40 mm stone aggregate as bottom layer up to 50% of the depth.

Document certified by PATIL MITHILESH JANARDHAN <a href="mithilesh.patingmail.com">mithilesh.patingmail.com</a>.

Name: PATIL MT ILESH JANARDIAN Designation associate Planner Organization: CIDCO

# Reference No.: CIDCO/BP-16781/TPO(NM & K)/2019/4906 Date: 22/6/2019

- 20 mm stone aggregate as lower middle layer up to 20% of the depth.
- c) Coarse sand as upper middle layer up to 20% of the depth.
- d) A thin layer of fine sand as top layer.
- e) Top 10% of the pits/trenches will be empty and a splash is to be provided in the portion in such a way that roof top water falls on the splash pad.
- f) Brick masonry is to be constructed on the exposed surface of pits/trenches and the cement mortar plastered.
  The depth of wall below ground shall be such that the wall prevents lose such that the projection of the wall above ground shall at least to 15 cms.
- Perforated concrete slabs shall be provided on the pits/trenches.
- v) If the open space surrounding the building is not paved, the top layer up to a sufficien depth shall be removed and refilled with course sand to allow percolation of rain water int ground.
- 2. The terrace shall be connected to the open well/bore well/storage tank/ recharge pit/trench b means of HDPE/pvc pipes through filter media. A valve system shall be provided to enable th first washings from roof or terrace catchment, as they would contain undesirable dirt. The mouth of all pipes and opening shall be covered with mosquito (insect) proof wire net. For the efficien discharge of rain water, there shall be at least two rain water pipes of 100mm dia. mt. for a roo area of 100 sq.mt.
- 3. Rain water harvesting structures shall be sited as not to endanger the stability of building o earthwork. The structures shall be designed such that no dampness is caused in any part of the walls or foundation of the building or those of an adjacent building.
- The water so collected/ recharged shall as far as possible be used for non-drinking and non cooking purpose.

Provided that when the rain water in exceptional circumstances will be utilized for drinking and/or cooking purpose, it shall be ensured that proper filter arrangement and the separate outlet for by

Document certified by PATIL MITHILESH JANARDHAN <mithilesh paylogmail com>

Name: PATIL MITTLE
JANARDIAN
Designation Associate
Planner
Organization: CIDCO

Reference No.: CIDCO/BP-16781/TPO(NM & K)/2019/4906

Date: 22/6/2019

passing the first rain-water has been provided.

Provided further that it will be ensured that for such use, proper disinfectants and the wat-

purification arrangements have been made.

Thanking You

Yours faithfully,

Document certified by PATIL MITHILESH JANARDHAN <mithilesh.pathagmail.com

Name : PATIL M JANARDIAN Designation sociat Planner Organization : CIDCO ociate

ASSOCIATE PLANNER (BP)

Page 13 of 12