SPECIFICATIONS OF PENINSULA PRAKRUTHI-ii

STRUCTURE

RCC Framed structure with 6" solid Block Masonary.

FLOORING

Vitrified tiles for living, dining room, Ceramic tiles for Bed Rooms and Kitchen, Toilet flooring with Antiskid ceramic tiles, pavers blocks for car parking.

DADOING

7'0" high wall dadoing in toilet, 2'0" high wall dadoing in kitchen

KITCHEN

20mm thick Granite slab with SS sink with drain board

SANITARY FITTING

White Colour Parry ware or equivalent ISI marks sanitary fixtures.

CP FITTINGS

ISI Branded Jaguar / Parry ware or equivalent CP Fittings for bathroom and Kitchen.

MAIN DOORS

Teak wood frame with teak wood panel door (STD Design), with polishing along with cp hardware fixtures and branded locks.

DOORS

Hard wood door frame with designed moduled skin shutter on the both side along with cp hardware fittings and branded lock.

WINDOWS

Three track UPVC window with mosquito mesh and 4 mm thick plain glass, MS grill for safety with enamel paint

INTERNAL STAIRCASE

20mm thick Sadarhalli granite for threads, 10mm thick for riser, with ms handrail.

WIRING

ISI Brand (Finolex or equivalent) FR Wires for lighting & heating circuits with ISI branded PVC conducts.

SWITCHES

Modular (Anchor/ Roma or equivalent) switches .Points as per Drawing (Extra points would be charged)

PAINTING (INTERNAL)

Two coat of putty would be applied followed by two coats of internal emulsion Roller Finish Paint for walls.

WATER SUPPLY

One common over head tank would be provided for the whole project. Water will be supplied from captive bore well.